

## HTU-350 Trailer Mount

### Pressure Pump Specifications

- Type: Positive displacement three plunger pump
- Operating Volume: 27 gpm (102 Lpm)
- Operating Pressure: 3,265 psi (22,511 kPa)

### Fill Pump Specifications

- Type: Centrifugal Pump
- Operating Volume: 350 ft of head pressure at 600 gpm (2,271 Lpm)
- Maximum Operating Pressure: 160 psi (1,130 kPa)

### Power Source Specifications

- Type: Duetz diesel engine rated at 207.5 hp at 2500 rpm (155 kW at 2500 rpm)
- Capacity: 75 gallons diesel (284 liters)

### Trailer Mount Specifications

- Type: Tandem axle rated at 10,000 lbs. (4,536 kgs.)
- Transport Width: 96" (2,438 mm)
- Transport Length: 204" (5,181 mm)
- Transport Height: 107" (2,718 mm)
- Approx. Shipping Weight: 7,200 lbs. (3,267 kgs.)
- Road Equipment and Safety Features: Trailer is equipped with a 2-5/16" dia. (58.75 mm) ball hitch, electric brakes, three point stabilizing jacks, and fully functional tail lights with brake and turn signals. Units also include an emergency breakaway kit with battery and safety chains.
- 20' suction hose and 6" valve included.



## HTU-350 Hydrostatic Fill and Testing Unit

